

批 App

华南国家计量测试中心 广东省计量科学研究院 GUANGDONG INSTITUTE OF METROLOGY



校准证书 CALIBRATION CERTIFICATE									
证书编号 CY Certificate No.	Q202211655				第 1 Page			3	页
委托方 Client	优利德科技	(中国)股	份有限	公司	~				
委托方联络信息 Contact Information	广东省东莞	市松山湖	园区工	AK IK	一路	6号			200
计量器具名称 Description	望远镜测距	仪	\bigcirc			1.50			200
型号/规格 Model/Type	LM800G	7		<i>b</i>	500	C. A.	5	52	
制造厂 Manufacturer	UNI-T		a. A.	50	C.M.	Э.	5	Ale	20 Mc
出厂编号 Serial No.	自编2204200	01		设备 Equi					197
接收日期 Date of Receipt	140 S	SUN A	2022	年 Y	04	月 M	01	日 D	5
结果 Results	见校准结果 Shown in the r		libratio	n					
校准日期 Date of Calibra	ation	en scent	2022	年 Y	04	月 M	20	日 D	Contra la
准人 proved Signatory <u></u> 升	wat	陈伟琪		ST IN AND AND AND AND AND AND AND AND AND AN				A A A A A A A A A A A A A A A A A A A	
Reviewed by	西湖湖	范斌斌		1400		书专用 Stamp		it was	
校准 Calibrated by 7 .		孙彦锋			ch-	- FF			

扫一扫查真伪

本中心地址:中国广州市广园中路松柏东街30号 邮政编码: 510405 电话: (8620)86594172 传真: (8620)86590743 投诉电话: (8620)36611242 E-mail: scm@scm.com.cn Add: No.30, Songbai East Street, Guangyuan Middle Road, Guangzhou, Guangdong, China Post Code: 510405 Tel: (8620)86594172 Fax: (8620)86590743 Complaint Tel: (8620)36611242 证书真伪查询: www.scm.com.cn; cert.scm.com.cn Certificate AuthenticityIdentify: www.scm.com.cn; cert.scm.com.cn

8220401069 1



 (50 ± 5) %

R.H.

3. 校准地点、环境条件: Place and environmental conditions of the calibration: 本中心测绘仪器实验室 地点 温度 (20.0±3.0) ℃ 相对湿度 (Survey Instrument Lab.) Place Temperature 4. 本次校准的技术依据:

Reference documents for the calibration: JJF1704-2018 望远镜式测距仪校准规范

5. 本次校准所使用的主要计量标准器具:

设备名称/型号规格	编号	证书号/有效期/溯源单位	计量特性
Name of Equipment	Serial No.	Certificate No./Due Date	Metrological
/Model/Type		/Traceability to	Characteristic
标准钢卷尺	190006	CJC202110312	$U = 5\mu m + 5 \times 10^{-6} L, k = 2$
Standard Steel Tape	High I	/2022-06-29	
/100 m		/本中心	
白云机场标准长度基线场	JX01等	JX2021-25号	U = (0.14 - 0.94) mm (k = 2)
Baiyun airport standard		/2024-08-24	
length baseline field		/自然资源第一测量队	and they can be the
/(24∽1008) m		and the second sec	

C.S. for Telescope Rangefinders

注: 1. 本证书校准结果只与受校准仪器有关。 The results relate only to the items calibrated.

Note: 2. 未经本机构书面批准,不得部分复制此证书。 This certificate shall not be reproduced except in full, without the written approval of our laboratory.

3. "委托方"、"委托方联络信息"由委托方提供, "制造厂"、"型号规格"、"出厂编号"以及"设备编号"为仪器上标注,委托方对上面内容如有异议,须在收到证书后二十个工作日内提出。

The information Client and Contact Information are provided by client, and the Manufacturer, Model/Type, Serial No. and Equipment No. are marked on the items. Client shall submit any objection within 20 working days after receiving the certificate for the information above.

4. 本次校准日期视为发布日期。 The calibration date is the date of issue of the certificate.



华南国家计量测试中心 东省计量科学研究院 SOUTH CHINA NATIONAL CENTER OF METROLOGY





CALIBRATION

校准结果 **RESULTS OF CALIBRATION**

证书编号 CYQ202211655 Certificate No.

原始记录号 CYQ202211655 Record No.

第3页,共3页 Page of

1 外观质量及各项功能: Appearance and functions: 符合要求 Pass

0.1 m 2 测量重复性(标准偏差): Repeatability of measurement (experimental standard deviation):

3 示值误差(长度):

Indication error(length):

受测点 (m)	示值误差(m)	受测点 (m)	示值误差(m)
Point	Indication error	Point	Indication error
10	-0.3	240	-3.0
20	-0.5	360	0.0
30	-0.7	552	-1.1
72	-0.3	792	+1.9
144	-0.2		

说明: Note:

1 本次室外检定地点: Field place of the verification

白云机场标准长度基线场

环境条件: Environmental condition

温度: 16℃ Temperature

2 示值误差(长度)测量结果的扩展不确定度: U = 0.4 mExpanded uncertainty of measurement for indication error(length)

包含因子 k=2Coverage factor

本证书中给出的扩展不确定度依据JJF1059.1-2012《测量不确定度评定与表示》评定,由合成标准不确 定度乘以包含概率约为95%时对应的包含因子k得到。

The expanded uncertainty given in this certificate is evaluated according to JJF 1059.1-2012 Evaluation and Expression of Uncertainty in Measurement, which is obtained by multiplying the combined standard uncertainty by the coverage factor k corresponding to the coverage probability of about 95%.

3 由于复校时间间隔的长短由仪器使用情况、使用者、仪器本身质量等诸因素所决定的,因此,送校单位 可根据实际情况自主决定复校时间间隔。建议不超过1年。更换重要部件、维修或对仪器性能有怀疑 时,应及时校准。

Since the calibration interval is depended on a number of factors, such as the use of the instrument, operation of the user, and the quality of the instrument itself, the next calibration date can be decided by the user according to the actual use. Next calibration for this instrument is proposed within 1 year. When replacing important parts, repairs, or doubts about the performance of the instrument, it should be calibrated in time.