

A25 series air quality meters are used to measure PM2.5 concentration. A25 series can be used in homes, offices, hotels, schools, factories, hospitals, restaurants, and other public places.

Features

Precise PM2.5 concentration based on pre-calibrated sensors

Temperature measurement (°C/°F)

Humidity measurement (A25D)

Emoticon display

LCD backlight and red backlight alarm

Battery status, auto power off



Specifications	Range	A25M	A25D
Certificates	CE, UKCA		
PM2.5 (ug/m ³)	0~100 101~400 401~500	±(10ug/m ³ +10dgts) ±(10%+30dgts) ±(10%+50dgts)	±(10ug/m ³ +10dgts) ±(10%+30dgts) ±(10%+50dgts)
Formaldehyde (mg/m ³)	0~2		
Temperature	-10°C~50°C	For reference only	±1°C
Humidity	5%~99%RH		±5%RH@30%~80%RH ±8%RH@<30%RH, >80%RH

Characteristics

Standard accessories	1m micro USB cable, wall mount (A25M), English manual
Power	A25M: 520mAh Li-ion battery; A25D: 1500mAh Li-ion battery
Display	A25M: 35 x 35mm; A25D: 42 x 65mm
Product size	A25M: 64 x 60 x 28mm; A25D: 75 x 55 x 130mm
Product net weight	A25M: 85g; A25D: 230g
Standard individual packing	Gift box
Standard quantity per carton	A25M: 20pcs; A25D: 5pcs
Standard carton measurement	A25M: 325 x 215 x 210mm; A25D: 360 x 185 x 140mm
Standard carton gross weight	A25M: 4.5kg; A25D: 2.35kg