



UT-C01 Hook type test clamps

- Specifications: Rod length 62mm, hook can extend to 7.5mm
- Safety level: CAT III 1000V 10A
- Features: With safety handle and spring hook type alligator clips
- Amount: 1 pair



UT-C02A Through hole alligator clips

- Specifications: Length 80mm, opening 36mm
- Safety level: CAT III 1000V/CAT IV 600V 10A
- Safety certificate: EN 61010-031:2015
- Amount: 1 pair



UT-C02B (M4) threaded bore alligator clips

- Specifications: Length 80mm, opening 36mm
- Safety level: CAT III 1000V/CAT IV 600V 10A
- Safety certificate: EN 61010-031:2015
- Amount: 1 pair



UT-C04A Through hole alligator clips

- Specifications: Length 75mm, opening 27mm
- Safety level: CAT III 1000V/CAT IV 600V 10A
- Safety certificate: EN 61010-031:2015
- Amount: 1 pair



UT-C05A (M4) threaded bore alligator clips (with protector)

- Specifications: Length 67mm, opening 8.3mm
- Safety level: CAT III 1000V/CAT IV 600V 10A
- Amount: 1 pair



UT-C05B Through hole alligator clips (with protector)

- Specifications: Length 71mm, opening 8.3mm
- Safety level: CAT III 1000V/CAT IV 600V 10A
- Amount: 1 pair



UT-C07 Multifunctional electric test clips

- Specifications: Rod length 110mm, adjustable clip length 8mm
- Safety level: CAT III 1000V/CAT IV 600V 5A
- Features: Standard transfer socket, adjustable multifunctional clips
- Amount: 1 pair



UT-C12 Through hole alligator clips (with protector)

- Specifications: Length 53mm, opening 6mm
- Amount: 1 pair



UT-L42 Kelvin clips double insulated wire

- Length: 1000mm
- Features and application: AV input lead, used for UT620A
- Amount: 1 pair



UT-L61 Kelvin clips

- Leads material: Double insulated wire
- Leads length: 600mm
- Application: UT612
- Amount: 1 pair