

UT120 series multimeters are designed for DIYers and electronics engineers to troubleshoot electronics systems development and electronics circuits. It is a simple and portable multimeter for every electronics engineer.



UT120C



Specifications	Range	UT120A	UT120B	UT120C
Certificates	CE, UKCA, cETLus (UT120A/UT120B)			
DC voltage (V)	600V	±(0.8%+1)	±(0.8%+1)	±(0.8%+1)
AC voltage (V)	600V	±(1.2%+3)	±(1.2%+3)	±(1.2%+3)
DC current (A)	400mA			±(1%+3)
AC current (A)	400mA			±(1.5%+5)
Resistance (Ω)	40MΩ	±(1%+2)	±(1%+2)	±(1%+2)
Capacitance (F)	100µF		±(4%+3)	±(4%+3)
Frequency (Hz)	100kHz	±(0.5%+3)	±(0.5%+3)	±(0.5%+3)
Display count	4000			
Category ratings	CAT II 600V			

Features	
Auto range	Duty cycle: 0.1%~99.9%
Diode	Auto power off
Continuity buzzer	Low battery indication: ≤2.4V
Data hold	Relative mode

Characteristics	
Standard accessories	Blister, English manual
Power	3V battery (CR2032)
Display	43 x 22mm
Product size	110 x 58.2 x 10.8mm
Product net weight	76g
Standard individual packing	Gift box
Standard quantity per carton	60pcs
Standard carton measurement	430 x 255 x 460mm
Standard carton gross weight	11.5kg