

UT125C is a pocket size, ergonomic and reliable multimeter with 4000 display counts. It is a useful tool for electronics DIYers working with low currents (<0.4A).

This product is CE/cETLus certified and complies with CAT III 600V.



UT125C

| Specifications | Range | Accuracy |
|-----------------------|------------------|-----------|
| Certificates | CE, UKCA, cETLus | |
| DC voltage (V) | 600V | ±(0.5%+5) |
| AC voltage (V) | 600V | ±(1.2%+5) |
| DC current (A) | 400mA | ±(1.8%+5) |
| AC current (A) | 400mA | ±(2%+8) |
| Resistance (Ω) | 40MΩ | ±(1%+5) |
| Capacitance (F) | 100μF | ±(4%+10) |
| Frequency (Hz) | 10Hz~60kHz | ±(0.1%+5) |
| Duty cycle | 20%~80% | Reference |
| Operating temperature | 0°C~50°C | |
| Category ratings | CAT III 600V | |

| Features | |
|------------------------|----------------------------|
| NCV | Diode test/Continuity test |
| Low battery indication | Data hold/backlight |

| Characteristics | |
|------------------------------|---------------------------|
| Standard accessories | Batteries, English manual |
| Power | 1.5V battery (R03) x 2 |
| Display | 38 x 23mm |
| Product size | 112 x 58 x 35mm |
| Product net weight | 180g |
| Standard individual packing | Gift box |
| Standard quantity per carton | 60pcs |
| Standard carton measurement | 500 x 290 x 280mm |
| Standard carton gross weight | 13.5kg |

