



UT136C+



| Specifications | Range | UT136B+ | UT136C+ |
|------------------------------------|-----------------------------|----------------|----------------|
| DC voltage (V) | 1000V | $\pm(0.7\%+3)$ | $\pm(0.7\%+3)$ |
| AC voltage (V) | 1000V | $\pm(1\%+3)$ | $\pm(1\%+3)$ |
| DC current (A) | 10A | $\pm(1\%+3)$ | $\pm(1\%+3)$ |
| AC current (A) | 10A | $\pm(1.2\%+5)$ | $\pm(1.2\%+5)$ |
| Resistance (Ω) | 40M Ω | $\pm(0.8\%+2)$ | $\pm(0.8\%+2)$ |
| Capacitance (F) | 40mF | $\pm(3\%+5)$ | $\pm(3\%+5)$ |
| Frequency (Hz) | 400Hz~40MHz | $\pm(0.1\%+4)$ | $\pm(0.1\%+4)$ |
| Temperature ($^{\circ}\text{C}$) | -40~1000 $^{\circ}\text{C}$ | | $\pm(1\%+3)$ |
| Temperature ($^{\circ}\text{F}$) | -40~1832 $^{\circ}\text{F}$ | | $\pm(1.5\%+5)$ |
| Display count | | 4000 | 4000 |
| NCV | | v | |
| Category ratings | CAT II 1000V, CAT III 600V | | |

| Features | |
|--------------------------------------|---|
| Equipped with 3mm protective sleeve | Measures up to 1000V and 10A AC/DC current |
| Quick sampling rate, up to 4 times/s | Large LCD display |
| Transistor measurement | Quick capacitor measurement (measures 1mF in 4 seconds) |
| Overload alarm | Diode/continuity buzzer |
| LCD backlight | Data hold/Auto power off |
| 2m drop proof | Low power consumption and auto power saving function |

| Characteristics | |
|------------------------------|--|
| Standard accessories | Batteries, test leads, temperature probe (UT136C+), English manual |
| Power | 1.5V battery (R6) x 2 |
| Display | 56.5 x 36mm |
| Product size | 175 x 83 x 53mm |
| Product net weight | 330g |
| Standard individual packing | Gift Box |
| Standard quantity per carton | 30pcs |
| Standard carton measurement | 390 x 355 x 355mm |
| Standard carton gross weight | 14.8kg |