

UT220 SERIES

2000A Digital Clamp Meters

UT220 series are 2000A AC/DC digital clamp meters. This series ensures stable performance, safety, and reliability for measuring up to 2000A AC (and DC for UT221) current. It is designed with over-load protection for all ranges, perfect for all professionals measuring currents up to 2000A (2500A for UT222).



- Auto range
- Diode
- Continuity buzzer
- Data hold
- MAX/MIN
- Low battery indication



● UT221

	Range	UT220	UT221	UT222
Certificates	CE, RoHS, cETLus			
AC current (A)	2000A 2500A	±(2.5%+5)	±(2.5%+5)	±(1.5%+5)
DC current (A)	2000A 2500A		±(2.5%+5)	±(1.5%+5)
AC voltage (V)	750V 1000V	±(1.2%+5)	±(1.2%+5)	±(1%+3)
DC voltage (V)	1000V	±(0.8%+1)	±(0.8%+1)	±(0.5%+2)
Resistance (Ω)	20MΩ 60MΩ 66MΩ	±(1%+2)		±(1%+2)
Capacitance (F)	60mF		±(1%+2)	±(3%+5)
Frequency (Hz)	20MHz 60MHz		±(0.1%+3)	±(0.1%+3)
Temperature	-40°C~1000°C -40°F~1832°F			±(1%+10) ±(1%+18)
Display count		2000	6000	6000
Jaw opening		63mm	63mm	63mm
True RMS			√	√
Duty cycle	10%~90%		√	√
AC+DC			√	√
Low pass filter			√	√
Inrush current			√	√
Relative mode			√	√
I-OUT function			√	√
Data storage				1000
Analog bar graph			66	61
Category ratings	CAT III 1000V, CAT IV 600V			
Power	9V battery (6F22)			
Display	43mm x 30mm			
Product net weight	UT220: 389g; UT221/UT222: 726g			
Product size	298mm x 107mm x 47mm			
Standard accessories	Test leads, output cable (UT221/UT222), thermocouple (UT222), English manual			
Standard individual packing	Gift box, carrying bag (UT220), tool box (UT221/UT222)			
Standard quantity per carton	UT220: 10pcs; UT221/UT222: 5pcs			
Standard carton measurement	UT220: 640mm x 305mm x 175mm; UT221/UT222: 510mm x 375mm x 320mm			
Standard carton gross weight	UT220: 7.52kg; UT221/UT222: 12.1kg			