# Technical Specifications

Specifications				
Models		UT665P	UT665P-5m	UT665P -10m
System	Screen Size	4.3"		
	System Languages	English		
	Screen Pixels	1280*720		
	Basic Functions	Screen rotation, Contrast adjustment, Black-white images, Color conversion, Image zoom-in and zoom-out, Screen brightness adjustment.		
Hose	Hose Material	Replaceable hardwire with aviation plug		
	Hose Length	1m	5m	10m
Lens	Lens Diameter	8mm		
	Light Sensor Chip	CMOS		
	Field of View (FOV)	70°		
	Depth of Field (DOF)	20~100mm		
	Adjustable LED Lights	4-Setting, 8 LEDs		
	Pixels	300K		
	IP Rating		IP67	
Battery	Battery	3.7V/2000mAh		
	Battery Life		6h	
	Lens Temperature		0°C~80°C	
Working Conditions	Working Temperature	0°C~45°C		
	Humidity	<90%RH, No condensation		
Characteristics				
Product Size		256x120x50mm		
Product Net Weight		About 270g(Hose not included)		
Standrad Accessories		Accessories List: Handheld Single Lens Industrial Borescope*1, Type-C Cable*1, Gift Box*1, User Manual*1, Blister Tray*1, Hook*1, Side Mirror*1, Magnet*1, Fixed Buckle*3.		
Standard Quantity Per Carton		20pcs		

### Applications









UNI-TREND TECHNOLOGY









Wide 178° angle of view, 1280\*720 HD image quality, Natural color rendition



#### HD Camera

300K HD Camera, High Brightness, Large Depth of Field



LED Flashlight

#### Screen rotation

More convenient viewing and operation



#### Multi-functional Accessories

Easy to operate in different complex conditions, locate and capture accurately.









#### IP67 Waterproof and Dustproof Lens

Support to work in damp environment, even under water



#### 2000mAh Rechargeable Li-ion Battery

Large storage, Long battery life, Type-C direct charging



## Aviation Plug, Replaceable Hose

1m, 5m, and 10m hoses are available





